

LEVITON

Applications Cookbook
Omnistat3 (RC500) Hospitality Thermostat & Guestroom Control

Version 4.0

FOR REFERENCE ONLY

TABLE OF CONTENTS



PAGE	DESCRIPTION
4	RC500 Hospitality Thermostat & Guestroom Master Controller—No New Wires
5	RC500 Hospitality Thermostat & Guestroom Master Controller—Lumina™ RF and Key Card Switch Option 1
6	RC500 Hospitality Thermostat & Guestroom Master Controller—Lumina™ RF and Key Card Switch Option 2
7	RC500 Hospitality Thermostat & Guestroom Master Controller with Dimming—Lumina™ RF and Hardwired Main Door Contact Option 1
8	RC500 Hospitality Thermostat & Guestroom Master Controller with Dimming—Lumina™ RF and Hardwired Main Door Contact Option 2
9	RC500 Hospitality Thermostat & Guestroom Master Controller with Dimming—LevNet RF™ 902MHz
10	RC500 Hospitality Thermostat & Guestroom Master Controller—Lumina™ RF and Key Card Switch (with additional battery powered Lumina RF sensors)
11	RC500 Hospitality Thermostat & Guestroom Master Controller—Lumina™ RF and Key Card Switch with Hardwired Balcony Door Contact
12	RC500 Hospitality Thermostat & Guestroom Master Controller—Lumina™ RF and Hardwired Main Door Contact Option 1
13	RC500 Hospitality Thermostat & Guestroom Master Controller—Lumina™ RF and Hardwired Main Door Contact Option 2
14	RC500 Hospitality Thermostat & Guestroom Master Controller—Lumina™ RF and Hardwired Main Door and Balcony Contact Option 1
15	RC500 Hospitality Thermostat & Guestroom Master Controller—Lumina™ RF and Hardwired Main Door and Balcony Contact Option 2
16	RC500 Hospitality Thermostat & Guestroom Master Controller—Lumina™ RF and Hardwired Main Door and Occupancy Sensor

OMNISTAT3 (RC500) HOSPITALITY THERMOSTAT & GUESTROOM CONTROL COOKBOOK NOTES



1. Refer to installation instructions for device-specific terminations
2. Refer to RC500 installation manual for HVAC connection instructions
3. Line feed 120/230/277VAC, 60Hz
4. Line feed shall not be connected to the RC500 Thermostat
5. All wiring on terminals 1-8 for the RC500 is 24VAC. Wiring to pin header is dry contact only.
6. Ground not shown. Ground devices per applicable national and local codes and best practices.
7. For emergency power situations, illustrations assume transfer switch by others upstream of shown devices
8. Line voltage load not to exceed contact rating per device specifications
9. Power packs receiving separate feeds for switched loads and self power must have both feeds on the same phase
10. All low-voltage loads not to exceed contact rating per device specifications
11. Maximum run length for analog wiring is 1,000' @ #18 AWG
12. Sensors wired in parallel will cause line voltage relay closure when occupancy is detected by any unit
Devices in series requiring contact closure from a single device, (clock input, demand response, emergency, etc.) must follow these wiring conventions: first device in sequence provides the +V to the triggering relay; signal from closure attached to all devices in sequence input; com from first device in sequence attached to com on all devices in sequence
13. Ultrasonic ceiling mount sensors should be located a minimum of six (6) feet from HVAC supply/return vents
14. Trough-mounted, pendant mounted and pendant-mounted indirect lighting sources affect the operation of locally mounted sensors.
Contractor is responsible for adjusting sensor locations to allow for proper operation.
15. Contractor is responsible for proper sensitivity and time delay settings for non-adaptive products, following the manufacturer's recommended placement, and field verification of circuits with respect to power pack placement
16. Contractor is responsible for coordinating the operational options of sensors and power packs with the specific work requirements:
 - Work relevant energy code requirements affect circuits to be controlled and their control characteristics
 - One power pack is required for each controlled circuit
17. - Refer to power pack data sheet for output and installation guide for maximum number of sensors connected to a power pack
 - If multiple circuits are to be controlled by a sensor, auxiliary relays may be used in conjunction with a power pack
18. Ceiling sensors mounted over doorways should be placed one (1) foot inside the threshold

19. Up to 100 Mark VII style ballasts may be controlled per daylighting zone by miniZ™
20. All relays shown in de-energized state
21. Individually cap off unused leads
22. One-line parenthesis use:
 - (x) - Function
 - (#) - Terminal
23. Plug load control—commercial receptacle P/Ns:
 - Standard duplex:
 - Split control (1 outlet) CR015-1PX, CR020-1PX
 - Full control (2 outlets) CR015-2PX, CR020-2PX
 - Decora:
 - Split control (1 outlet) 16252-1PX, 16352-1PX
 - Full control (2 outlets) 16252-2PX, 16352-2PX

DRAWING SYMBOLS

⊕ No connection




⊖ Connection



DRAWING ABBREVIATIONS

LC	LumaCan
LV	Low voltage
HV	High voltage switch (maintained)
LVM	Low voltage switch (momentary)- equal to Leviton 1081 (toggle) or Leviton 56081 (Decora)
LVT	Low voltage switch (maintained)-equal to Leviton 12021-2 (toggle) or Leviton 56021-2 (Decora)
LV2	IRC low voltage switch
UON	Unless otherwise noted
BLK	Black
WHT	White
BLU	Blue
YEL	Yellow
ORG	Orange
VIO	Violet
BRN	Brown


RC500 HOSPITALITY THERMOSTAT & GUESTROOM MASTER CONTROLLER—NO NEW WIRES




NOTES:

1. MINIMUM SYSTEM REQUIREMENTS FOR AUTOMATED OCCUPANCY/VACANCY ROOM CONTROL: OMNISTAT 3 (RC500), DOOR/WINDOW SENSOR, (LURDW).

RC500 HOSPITALITY THERMOSTAT & GUESTROOM MASTER CONTROLLER— LUMINA RF AND KEY CARD SWITCH (OPTION 1)





- RESTRICTIONS:** SYSTEMS THAT WILL NOT WORK WHEN HVAC TERMINAL 1 USED:
- TWO SPEED HEAT PUMP (3 STAGE HEAT / 2 STAGE COOL)
 - SINGLE STAGE CONVENTIONAL (1 STAGE HEAT/ 1 STAGE COOL) WITH 3 SPEED FAN
 - TWO STAGE CONVENTIONAL (2 STAGE HEAT/ 2 STAGE COOL)
 - SINGLE SPEED HEAT PUMP (2 STAGE HEAT/ 1 STAGE COOL) WITH 2 SPEED FAN
 - 2 PIPE WITH 3 SPEED FAN
 - 4 PIPE WITH 3 SPEED FAN



NOTES:

1. MINIMUM SYSTEM REQUIREMENTS FOR AUTOMATED OCCUPANCY/VACANCY ROOM CONTROL: OMNISTAT 3 (RC500), HARD-WIRED KEYCARD SWITCH (HKSWP)



RC500 HOSPITALITY THERMOSTAT & GUESTROOM MASTER CONTROLLER— LUMINA RF AND KEY CARD SWITCH (OPTION 2)




NOTES:

1. MINIMUM SYSTEM REQUIREMENTS FOR AUTOMATED OCCUPANCY/VACANCY ROOM CONTROL: OMNISTAT 3 (RC500), HARD-WIRED KEYCARD SWITCH (HKSWP)

RC500 HOSPITALITY THERMOSTAT & GUESTROOM MASTER CONTROLLER WITH DIMMING— LUMINA RF AND HARDWIRED MAIN DOOR CONTACT (OPTION 1)




- RESTRICTIONS:** SYSTEMS THAT WILL NOT WORK WHEN HVAC TERMINAL 1 USED:
- TWO SPEED HEAT PUMP (3 STAGE HEAT / 2 STAGE COOL)
 - SINGLE STAGE CONVENTIONAL (1 STAGE HEAT/ 1 STAGE COOL) WITH 3 SPEED FAN
 - TWO STAGE CONVENTIONAL (2 STAGE HEAT/ 2 STAGE COOL)
 - SINGLE SPEED HEAT PUMP (2 STAGE HEAT/ 1 STAGE COOL) WITH 2 SPEED FAN
 - 2 PIPE WITH 3 SPEED FAN
 - 4 PIPE WITH 3 SPEED FAN



NOTES:

1. MINIMUM SYSTEM REQUIREMENTS FOR AUTOMATED OCCUPANCY/VACANCY ROOM CONTROL: OMNISTAT 3 (RC500), HARD-WIRED MAIN ENTRANCE DOOR SENSOR/SWITCH.




RC500 HOSPITALITY THERMOSTAT & GUESTROOM MASTER CONTROLLER WITH DIMMING— LUMINA RF AND HARDWIRED MAIN DOOR CONTACT (OPTION 2)



NOTES:

1. MINIMUM SYSTEM REQUIREMENTS FOR AUTOMATED OCCUPANCY/VACANCY ROOM CONTROL: OMNISTAT 3 (RC500), HARD-WIRED MAIN ENTRANCE DOOR SENSOR/SWITCH.




RC500 HOSPITALITY THERMOSTAT & GUESTROOM MASTER CONTROLLER WITH DIMMING— LEVNET RF 902 MHz



NOTES:

1. MINIMUM SYSTEM REQUIREMENTS FOR AUTOMATED OCCUPANCY/VACANCY ROOM CONTROL: OMNISTAT 3 (RC500), HARD-WIRED KEYCARD SWITCH (HKSWP)



RC500 HOSPITALITY THERMOSTAT & GUESTROOM MASTER CONTROLLER— LUMINA RF AND KEY CARD SWITCH (WITH ADDITIONAL BATTERY POWERED LUMINA RF SENSORS)



NOTES:

1. MINIMUM SYSTEM REQUIREMENTS FOR AUTOMATED OCCUPANCY/VACANCY ROOM CONTROL: OMNISTAT 3 (RC500), HARD-WIRED KEYCARD SWITCH (HKSWP)

RC500 HOSPITALITY THERMOSTAT & GUESTROOM MASTER CONTROLLER— LUMINA RF AND KEY CARD SWITCH WITH HARDWIRED BALCONY DOOR CONTACT






- RESTRICTIONS:** SYSTEMS THAT WILL NOT WORK WHEN HVAC TERMINAL 1 USED:
- TWO SPEED HEAT PUMP (3 STAGE HEAT / 2 STAGE COOL)
 - SINGLE STAGE CONVENTIONAL (1 STAGE HEAT/ 1 STAGE COOL) WITH 3 SPEED FAN
 - TWO STAGE CONVENTIONAL (2 STAGE HEAT/ 2 STAGE COOL)
 - SINGLE SPEED HEAT PUMP (2 STAGE HEAT/ 1 STAGE COOL) WITH 2 SPEED FAN
 - 2 PIPE WITH 3 SPEED FAN
 - 4 PIPE WITH 3 SPEED FAN

NOTES:

1. MINIMUM SYSTEM REQUIREMENTS FOR AUTOMATED OCCUPANCY/VACANCY ROOM CONTROL: OMNISTAT 3 (RC500), HARD-WIRED KEYCARD SWITCH (HKSWP)



RC500 HOSPITALITY THERMOSTAT & GUESTROOM MASTER CONTROLLER— LUMINA RF AND HARDWIRED MAIN DOOR CONTACT (OPTION 1)



NOTES:


1. MINIMUM SYSTEM REQUIREMENTS FOR AUTOMATED OCCUPANCY/VACANCY ROOM CONTROL: OMNISTAT 3 (RC500), HARD-WIRED MAIN ENTRANCE SENSOR/SWITCH.

RC500 HOSPITALITY THERMOSTAT & GUESTROOM MASTER CONTROLLER— LUMINA RF AND HARDWIRED MAIN DOOR CONTACT (OPTION 2)



RESTRICTIONS: SYSTEMS THAT WILL NOT WORK WHEN HVAC TERMINAL 1 USED:



- TWO SPEED HEAT PUMP (3 STAGE HEAT / 2 STAGE COOL)
- SINGLE STAGE CONVENTIONAL (1 STAGE HEAT/ 1 STAGE COOL) WITH 3 SPEED FAN
- TWO STAGE CONVENTIONAL (2 STAGE HEAT/ 2 STAGE COOL)
- SINGLE SPEED HEAT PUMP (2 STAGE HEAT/ 1 STAGE COOL) WITH 2 SPEED FAN
- 2 PIPE WITH 3 SPEED FAN
- 4 PIPE WITH 3 SPEED FAN




NOTES:

1. MINIMUM SYSTEM REQUIREMENTS FOR AUTOMATED OCCUPANCY/VACANCY ROOM CONTROL: OMNISTAT 3 (RC500), HARD-WIRED MAIN ENTRANCE SENSOR/SWITCH.

RC500 HOSPITALITY THERMOSTAT & GUESTROOM MASTER CONTROLLER— LUMINA RF AND HARDWIRED MAIN DOOR AND BALCONY CONTACT (OPTION 1)





- RESTRICTIONS:** SYSTEMS THAT WILL NOT WORK WHEN HVAC TERMINAL 1 USED:
- TWO SPEED HEAT PUMP (3 STAGE HEAT / 2 STAGE COOL)
 - SINGLE STAGE CONVENTIONAL (1 STAGE HEAT/ 1 STAGE COOL) WITH 3 SPEED FAN
 - TWO STAGE CONVENTIONAL (2 STAGE HEAT/ 2 STAGE COOL)
 - SINGLE SPEED HEAT PUMP (2 STAGE HEAT/ 1 STAGE COOL) WITH 2 SPEED FAN
 - 2 PIPE WITH 3 SPEED FAN
 - 4 PIPE WITH 3 SPEED FAN




NOTES:
1. MINIMUM SYSTEM REQUIREMENTS FOR AUTOMATED OCCUPANCY/VACANCY ROOM CONTROL: OMNISTAT 3 (RC500), HARD-WIRED MAIN ENTRANCE SENSOR/SWITCH.

RC500 HOSPITALITY THERMOSTAT & GUESTROOM MASTER CONTROLLER— LUMINA RF AND HARDWIRED MAIN DOOR AND BALCONY CONTACT (OPTION 2)




- RESTRICTIONS:** SYSTEMS THAT WILL NOT WORK WHEN HVAC TERMINAL 1 USED:
- TWO SPEED HEAT PUMP (3 STAGE HEAT / 2 STAGE COOL)
 - SINGLE STAGE CONVENTIONAL (1 STAGE HEAT/ 1 STAGE COOL) WITH 3 SPEED FAN
 - TWO STAGE CONVENTIONAL (2 STAGE HEAT/ 2 STAGE COOL)
 - SINGLE SPEED HEAT PUMP (2 STAGE HEAT/ 1 STAGE COOL) WITH 2 SPEED FAN
 - 2 PIPE WITH 3 SPEED FAN
 - 4 PIPE WITH 3 SPEED FAN



- NOTES:
1. MINIMUM SYSTEM REQUIREMENTS FOR AUTOMATED OCCUPANCY/VACANCY ROOM CONTROL: OMNISTAT 3 (RC500), HARD-WIRED MAIN ENTRANCE SENSOR/SWITCH.

RC500 HOSPITALITY THERMOSTAT & GUESTROOM MASTER CONTROLLER— LUMINA RF AND HARDWIRED MAIN DOOR AND OCCUPANCY SENSOR



RESTRICTIONS: SYSTEMS THAT WILL NOT WORK WHEN HVAC TERMINAL 1 USED:

- TWO SPEED HEAT PUMP (3 STAGE HEAT / 2 STAGE COOL)
- SINGLE STAGE CONVENTIONAL (1 STAGE HEAT/ 1 STAGE COOL) WITH 3 SPEED FAN
- TWO STAGE CONVENTIONAL (2 STAGE HEAT/ 2 STAGE COOL)
- SINGLE SPEED HEAT PUMP (2 STAGE HEAT/ 1 STAGE COOL) WITH 2 SPEED FAN
- 2 PIPE WITH 3 SPEED FAN
- 4 PIPE WITH 3 SPEED FAN

NOTES:
1. MINIMUM SYSTEM REQUIREMENTS FOR AUTOMATED OCCUPANCY/VACANCY ROOM CONTROL: OMNISTAT 3 (RC500), HARD-WIRED MAIN ENTRANCE SENSOR/SWITCH.



Leviton Manufacturing Co., Inc. Global Headquarters

201 North Service Road, Melville, NY 11747-3138 **tel** 800-323-8920 **fax** 800-832-9538 **tech line** (8:30AM-7:00PM ET Mon-Fri) 800-824-3005

Leviton Manufacturing Co., Inc. Energy Management, Controls and Automation

4330 Michoud Blvd., New Orleans, LA, 70129 **tel** 504-736-9810 **fax** 504-253-2954 **tech line** (8:30AM-7:00PM ET Mon-Fri) 800-824-3005

Visit our Website at: www.leviton.com/luminarf

©2017 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.

G-9575C/J17-AA
REV OCT 2017