

JC71812BLK

ToughBay Circular 230W 23,700lm 5700K IP65 105° Dimmable Black inc Hook



Features & Benefits

5 year extended warranty, including 2 year on-site support

105° beam angle without reflector

Supplied with mounting ring and IP67 connector as standard

60° reflector beam angle option

Suitable for high mounting industrial applications

IP65 - Suitable for areas with high salt/moisture content

1-10V dimmable as standard

General Information

Product Group	LED - Surface
Product Range	Toughbay
Trade Name	Toughbay

JCC Lighting

Innovation Centre, Beeding Close, Southern Cross
Trading Estate, Bognor Regis, West Sussex, PO22 9TS
Company Registration Number: 03044848 | VAT Number: 918544112
T: 01243 838999 | F: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk

Light Source	LED
Light Source Features	Crisp White
Lighting Product Type	Ceiling Mount
Product Shape	Round
Mounting	Surface Mounted
Product Weight	7.4Kg approx
Color Finish	Black
Recommended Product Location	Medium height mounting industrial applications. Suitable for areas with high salt/moisture content.
Method Of Fix	Suspension eye(supplied) Surface bracket(optional)
Max Angle Of Tilt & Rotation	180° with surface bracket only
IP Rating	IP65
Environment	Indoor
Suitable For Zones	Zone 1
Luminaire Accessories	JC71851 / JC71852BLK / JC71850 / LEV71904
Dimming Protocol Compatibility	1-10V
Driver Manufacturer	Meanwell
LED Manufacturer/Type	Nichia 3030 / Nichia

Electrical

A Cable	Yes
Voltage Rating	100-240
Secondary Running Current	2.5 to 5 Amps
Primary Running Current	2.0 Amps
Operating Frequency (Hz)	50/60Hz
CC or CV	Constant current

JCC Lighting

Innovation Centre, Beeding Close, Southern Cross
Trading Estate, Bognor Regis, West Sussex, PO22 9TS
Company Registration Number: 03044848 | VAT Number: 918544112

T: 01243 838999 | F: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk

Luminaire Circuit Wattage	230W
Sec - Voltage (V)	48V DC
Class	Class I, requires earth
Total Harmonic Distortion (THD)%	20%
EMC Compliant (EN55015)	Yes
Power Factor Correction	0.95
Input Electrical Connections	Live, Earth, Neutral (pre-wired flex)
Dimmable	Yes, 1-10V only

Thermals

Max Luminaire Ambient Temp.	60°C
Max Driver/Ballast Ambient Temp.	80°C
Thermal Cut Out	100°C + 10%
Insulation Coverage	Do not cover
Minimum Free Air Space	100mm

Performance Data

Energy Rating	A+
Actual Lumen Output	23700
Lumen Output	18001-35000
Lumens Per Circuit Watt	103 lm/W
LED Life (Hours)	50,000 to L70
Color Rendering Index	80-89
CRI: Ra	80
Correlated Color Temperature	5700K
Light Distribution Detail	105-degree

JCC Lighting

Innovation Centre, Beeding Close, Southern Cross
Trading Estate, Bognor Regis, West Sussex, PO22 9TS
Company Registration Number: 03044848 | VAT Number: 918544112

T: 01243 838999 | F: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk

LOR (Light Output Ratio) %	100%
Photometry Available	Yes

Construction

Primary Material	Aluminum
Lens	Polycarbonate
Heat Sink	Cast aluminium
Driver Housing	Aluminium
Rim Or Attachment	Spun aluminium

Packaging

Luminaire Carton Dimensions	465mm x 465mm x 200mm
Quantity Per Outer Carton	1
Bar Code EAN Number	5052544046261
Packaged Weight	8.2Kg approx

Standards & Approvals

Listings	CE
Manufactured In Accordance To	BS EN 60598-2-1
CE Marked	Yes
Batch Coded	Yes
Certificate Of Conformity	Yes, available on request
Accredited Members	LIA, ISO9001:2015, ISO14001:2015

Datasheet generated from https://www.electrika.cloud on 03 August 2018 02:14:21

